



cctvtrade.com

Photo-Scan (2006) Ltd

57 Boston Road : Mt Eden : PO Box 4429 : Auckland

Telephone (09) 302 2181 : Facsimile (09) 3022473

EMAIL: sales@cctvtrade.com WEB http://www.cctvtrade.com

Colour Hi-Impact Vandal Resistant Dome Camera Tayama C3834-62C5V3 Auto-Iris Vari-Focal Lens



Solid cast base and super-strength dome for risk situations!

| | |
|------------------------------|--------------------------------------|
| Image Pickup Device: | Sony 1/3" Super HAD CCD |
| Effective Picture Elements: | 500 x 582 (H x V) |
| Horizontal Resolution: | 420 Lines |
| Minimum Illumination: | 0.05 Lux, F=1.2 |
| S/N Ratio: | More than 48dB |
| Auto Electronic Shutter: | 1/50s to 1/110000s On/Off switchable |
| Auto Iris Control: | DC Drive |
| Flicker less Mode: | 1/120s On/Off switchable |
| Gamma Characteristic: | 0.45 |
| Lens Furnished: | Vari-Focal with DC Drive Iris |
| Focal Length and Aperture: | f=3.5mm to 8.0mm |
| Angle Field of View: | 78.9 to 58.3 degrees horizontal |
| Auto Gain Control: | High / Low switchable |
| Auto White Balance: | Mutli-Color Temperature (MCT-AWB) |
| Back Light Compensation: | On / Off switchable |
| Video Output: | 1 Vp-p, 75 Ohms |
| Power Consumption: | AC24V 1.9W or 12V DC 2.16W |
| Operating Temperature Range: | -10 C to +50 C |
| Dimensions: | 140mm Dia, 98.5mm Height |
| Weight: | 2 kgs |

www.cctvtrade.com