



cctvtrade.com

Photo-Scan (2006) Ltd

57 Boston Road : Mt Eden : PO Box 4429 : Auckland
Telephone (09) 302 2181 : Facsimile (09) 3022473
EMAIL sales@cctvtrade.com WEB <http://www.cctvtrade.com>



GL-615-3824 Vandalproof Dome Camera

PICK-UP ELEMENT:	1/3 INCH SONY CCD IMAGE SENSOR
SIGNAL MODE:	PAL
NUMBER OF PIXELS:	712(H) x 582(V)
RESOLUTION:	420 TV LINES
MINIMUM ILLUMINATION:	0.5 LUX, F=1.2
S/N RATIO:	MORE THAN 48dB (AGC OFF)
AUTO ELECTRONIC SHUTTER:	1/50s TO 1/110,000s
GAIN CONTROL:	AGC (FULL AUTO)
BACK LIGHT COMPENSATION:	FULL AUTO
BOARD LENS:	f3.7mm PIN HOLE LENS
WHITE BALANCE:	MCT-AWB (MULTI-COLOR TEMPERATURE AUTO WHITE BALANCE)
VIDEO OUTPUT:	1.0 Vp-p COMPOSITE VIDEO AT 75 OHMS
POWER SOURCE:	DC12V±10%
CURRENT CONSUMPTION:	110mA
STORAGE TEMPERATURE:	-30°C to +60°C
OPERATING TEMPERATURE:	-10°C to +45°C
DIMENSIONS:	143(W) x 80(H)mm
NET WEIGHT:	600g